

B6657

Fabric / Tissu / Weefsel / Gewebe	DIN ISO 2060 : 1994	100 % PES / 1670 dtex
Total weight / Poids total / Gewicht totaal / Totalgewicht	ISO 2286/2 : 2016	1150 g/m²
Coating		PVC
Weaving style / Armature / Binding / Bindung	DIN ISO 9354	P2/2
Characteristics Caractéristiques Eigenschappen Eigenschaften		ABUV
Lacquering / Vernis / Lackierung		1/1
Comment / Remarque / Opmerking / Kommentar		SIOFLUO
Embossing / Calandre / Kalander / Prägung		Glossy
Breaking strength Warp Résistance rupture Chaîne Treksterkte Ketting Höchstzugkraft Kette	ISO 1421/1 : 2016	5500 N/5cm
Breaking strength Weft Résistance rupture Trame Treksterkte Inslag Höchstzugkraft Schuss	ISO 1421/1 : 2016	5000 N/5cm
Tear strength Warp Résistance à la déchirure Chaîne Scheurweerstand Ketting Weiterreisskraft Kette	DIN 53363 : 2003	800 N
Tear strength Weft Résistance à la déchirure Trame Scheurweerstand Inslag Weiterreisskraft Schuss	DIN 53363 : 2003	800 N
Adhesion / Adhérence / Hechting / Haftung	ISO 2411 : 2017	120 N/5cm
Temperature resistance Tenue à la température Temperatuursbestendigheid Temperatursbeständigkeit	EN 1876/1 : 1998	-30/+70 °C
Light fastness (Except white and (half-)transparent) Tenue à la lumière (Excepté en blanc et (semi-)transparent) Lichtechtheid (Uitgezonderd wit en (half-)transparent) Lichtechtheid (Ausnahme weiss und (semi-)transparant)	ISO 105 B02 : 2014	7-8
Gas permeability Perméabilité au gaz Gaspermeabiliteit Gaspermeabilität	ISO 15105/1 : 2007 - DIN 53380/2 : 2006	< 400 cm³/m².bar.d

"Biogas fabrics are intended to be installed only by registered and experienced manufacturers of biogas installations, who are aware of the specifications and the limitations of the materials used. Direct contact of inner lung material with the reactive fermentation mixtures should be avoided. For further technical information on the membranes and its compatibility, we refer to the technical staff of Sioen Industries."

B6657

Flex resistance Résistance à la pliure Plooiweerstand Knickverhalten	ISO 7854/B : 1995	100000 flex
Fire behaviour_FR / Reaction au feu_FR / Brandgedrag_FR / Brennverhalten_FR	NF P 92-507:2004	M2
Fire behaviour_DE / Réaction au feu_DE / Brandgedrag_DE / Brennverhalten_DE	DIN 4102-1 : 1998	B1
Reaction to fire_EU / Reaction au feu_EU / Reactie bij brand_EU / Brennverhalten_EU	EN 13501-1 : 2018	B-s2,d0
Application -> Agriculture/BiogasInstallation/HydrolysisResistant		

"Biogas fabrics are intended to be installed only by registered and experienced manufacturers of biogas installations, who are aware of the specifications and the limitations of the materials used. Direct contact of inner lung material with the reactive fermentation mixtures should be avoided. For further technical information on the membranes and its compatibility, we refer to the technical staff of Sioen Industries."